

# MAXO<sub>2</sub>+AE Oxygen Analyzer

# **Technical Data**



The  $MAXO_2 + AE$  is an oxygen analyzer that measures the oxygen concentration in a flow of gas from a medical gas source or through a medical gas-flow device such as a ventilator or anesthesia system, or within an infant incubator. It is handheld and rugged to suit the needs of portable use. The  $MAXO_2 + AE$ comes equipped with a two-year warranty on both analyzer and sensor.

### **Key features**

- One-touch calibration, with reminder
- Long battery life (approx. 5,000 hrs)
- Impact resistant and drip proof
- External MAX-250E Oxygen Sensor



# **Specifications**

| Measurement range          | 0 % to100 %  |
|----------------------------|--|
| Resolution                 | 0.1 %  |
| Accuracy and linearity     | 1 % of full scale at constant temperature, RH and pressure when calibrated at full scale |
| Total accuracy             | ± 3 % actual oxygen level over full operating range                                      |
| Response time              | 90 % of final value in approx. 15 sec at 23 °C   |
| Warm-up time               | None required  |
| Power supply               |  |
| Battery life               | Approx. 5000 hours with continuous use   |
| Low battery indication     | "BAT" icon displayed on LCD  |
| Sensor type                | Maxtec® MAX-250E for AE model  |
| Expected sensor life       | >900,000 02 % hours minimum, two years in typical medical applications                   |
| Power requirements         | Two, AA Alkaline batteries   |
| Environmental requirements |  |
| Operating temperature      | 15 °C to 40 °C (59 °F to 104 °F)   |
| Storage temperature        | -15 °C to 50 °C (5 °F to 122 °F)   |
| Atmospheric pressure       | -800 mBar to 1013 mBar   |
| Relative humidity          | Operating range: 0 % to 95 % (non-condensing)  |
| General information        |  |
| Dimensions (LxWxH)         | 38 mm x 76 mm x 914 mm (1.5 in x 3 in x 36 in)   |
| Weight                     | 285 g (0.6 lb)   |

## **Ordering information**

Model MAXO, +AE Oxygen Analyzer

### **Standard accessories**

**Users Manual** MAX-250 External Oxygen Sensor **Oxygen Sensor Cable** VTMOB-4401 Breathing Circuit "tee"

#### About Fluke Biomedical

About Fluke Biomedical Fluke Biomedical is the world's leading manufacturer of quality biomedical test and simulation products. In addition, Fluke Biomedical provides the latest medical imaging and oncology quality-assurance solutions for regulatory compliance. Highly credentialed and equipped with a NVLAP Lab Code 200566-0 accredited laboratory, Fluke Biomedical also offers the best

Today, biomedical personnel must meet the increasing regulatory pressures, higher quality standards, and rapid technological growth, while performing their work faster and more efficiently than ever. Fluke Biomedical provides a diverse range of software and hardware tools to meet today's challenges.

Fluke Biomedical Regulatory Commitment As a medical test device manufacturer, we recognize and follow certain quality standards and certifications when developing our products. We are ISO 9001 and ISO 13485 medical device certified and our products are: • CE Certified, where required • NIST Traceable and Calibrated • UL, CSA, ETL Certified, where required • NRC Compliant, where required

#### Fluke Biomedical.

Better products. More choices. One company.

#### Fluke Biomedical

6045 Cochran Road Cleveland, OH 44139-3303 U.S.A.

Fluke Biomedical Europe Science Park Eindhoven 5110 5692EC Son, The Netherlands

For more information, contact us: In the U.S.A. (800) 850-4608 or Fax (440) 349-2307 In Europe/M-East/Africa +31 40 267 5435 or Fax +31 40 267 5436 From other countries +1 (440) 248-9300 or Fax +1 (440) 349-2307 Email: sales@flukebiomedical.com Web access: www.flukebiomedical.com

©2006-2011 Fluke Biomedical. Specifications subject to change without notice. Printed in U.S.A. 1/2011 2817978B D-EN-N

Modification of this document is not permitted without written permission from Fluke Corporation.